

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: P313 GLOSS YELLOW PAINT 400ML RAL 1007

Article number: CODE P313

Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation Paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Tygris Industrial
Unit 31
Kyle Road Industrial Estate
Irvine
Ayshire
KA12 8LE
Tel +44 (0) 1294 311 066
Fax +44 (0) 1294 277 115
Email technical@tygrisindustrial.com

Further information obtainable from: Technical Department

Emergency telephone number: Tel +44 (0) 1294 311 066

2. Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame
Flam. Aerosol 1 H222 Extremely flammable aerosol.

GHS05 corrosion
Eye Dam. 1 H318 Causes serious eye damage.

GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant
R36: Irritating to eyes.



F+; Extremely flammable
R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
Has a narcotizing effect.

Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements




| | |
|--|--|
| Labelling according to EU guidelines: | The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. |
| Code letter and hazard designation of product: | Xi Irritant F+ Extremely flammable |
| Risk phrases: | 12 Extremely flammable. 36 Irritating to eyes. 66 Repeated exposure may cause skin dryness or cracking. 67 Vapours may cause drowsiness and dizziness. |
| Safety phrases: | 2 Keep out of the reach of children. 16 Keep away from sources of ignition - No smoking. 23 Do not breathe aerosol. 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. 46 If swallowed, seek medical advice immediately and show this container or label. 51 Use only in well-ventilated areas. |
| Special labelling of certain preparations: | Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. |
| Classification in accordance with Directive 75/324/EEC: | Extremely flammable |
| Other hazards | |
| Results of PBT and vPvB assessment | |
| PBT: | Not applicable. |
| vPvB: | Not applicable. |

3. Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.


Dangerous components:

| | |
|--|---|
| CAS: 67-64-1 EINECS: 200-662-2 20-25% | acetone  Xi R36  F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 |
| CAS: 115-10-6 EINECS: 204-065-8 20-25% | dimethyl ether  F+ R12 Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas, H280 |


CAS: 123-86-4
EINECS: 204-658-1
10-12.5%

n-butyl acetate
R10-66-67
Flam. Liq. 3, H226
STOT SE 3, H336


CAS: 74-98-6
EINECS: 200-827-9
5-10%


propane
 F+ R12
Flam. Gas 1, H220
Press. Gas, H280

CAS: 108-65-6
EINECS: 203-603-9
5-10%



2-methoxy-1-methylethyl acetate
 Xi R36
R10
Flam. Liq. 3, H226

CAS: 106-97-8
EINECS: 203-448-7
5-10%


butane
 F+ R12
Flam. Gas 1, H220
Press. Gas, H280

isobutaan (bevattend < 0,1 % butadien (203-450-8))
 F+ R12
Flam. Gas 1, H220
Press. Gas, H280



CAS: 71-36-3
EINECS: 200-751-6
2.5-5%

butan-1-ol
 Xn R22
 Xi R37/38-41
R10-67
Flam. Liq. 3, H226
Eye Dam. 1, H318
Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335+H336




CAS: 9004-70-0
2.5-5%

Nitrocellulose (nitrogen content <12.6%)
 F R11
Flam. Sol. 1, H228

CAS: 67-63-0
EINECS: 200-661-7
1-2.5%

propan-2-ol
 Xi R36
 F R11
R67
Flam. Liq. 2, H225
Eye Irrit. 2, H319; STOT SE 3, H336

CAS: 64742-95-6
EINECS: 265-199-0
0.1-1%

Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)
 Xn R65
 Xi R37
 N R51/53
R10-66-67
Carc. Cat. 2, Muta. Cat. 2
Flam. Liq. 3, H226
Asp. Tox. 1, H304
Aquatic Chronic 2, H411
STOT SE 3, H335+H336

Additional information:

For the wording of the listed risk phrases refer to section 16.

4. First aid measures

Description of first aid measures

| | |
|---|--|
| After inhalation: | Supply fresh air; consult doctor in case of complaints |
| After skin contact: | Generally the product does not irritate the skin. |
| After eye contact: | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. |
| After swallowing: | Drink plenty of water and provide fresh air. Call for a doctor immediately. |
| Information for doctor: | |
| Most important symptoms and effects, both acute and delayed | No further relevant information available. |
| Indication of any immediate medical attention and special treatment needed | No further relevant information available. |

5. Firefighting measures

Extinguishing media

| | |
|--|---|
| Suitable extinguishing agents: | CO ₂ , powder or water spray. Fight larger fires with water spray or alcohol resistant foam. |
| For safety reasons unsuitable extinguishing agents: | Water with full jet |
| Special hazards arising from the substance or mixture | No further relevant information available. |
| Advice for firefighters | |
| Protective equipment: | No special measures required. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Ensure adequate ventilation Keep away from ignition sources. |
| Environmental precautions: | Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. |
| Methods and material for containment and cleaning up: | Ensure adequate ventilation. |
| Reference to other sections | See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. |

7. Handling and storage

Handling:

| | |
|---|--|
| Precautions for safe handling | No special measures required. Ensure good ventilation/exhaustion at the workplace. |
| Information about fire - and explosion protection: | Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. |

Conditions for safe storage, including any incompatibilities

Storage:

| | |
|--|--|
| Requirements to be met by storerooms and receptacles: | Store in a cool location. Observe official regulations on storing packagings with pressurized containers. |
| Information about storage in one common storage facility: | Not required. |
| Further information about storage conditions: | Protect from heat and direct sunlight. |
| Specific end use(s) | No further relevant information available. |

8. Exposure controls/personal protection

| | |
|---|------------------------------|
| Additional information about design of technical facilities: | No further data; see item 7. |
|---|------------------------------|

Control parameters

| | |
|---|--|
| Ingredients with limit values that require monitoring at the workplace: | 67-64-1 acetone |
| | WEL () Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm |
| | 115-10-6 dimethyl ether |
| | WEL () Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm |
| | 123-86-4 n-butyl acetate |
| | WEL () Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
| | 108-65-6 2-methoxy-1-methylethyl acetate |
| | WEL () Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk |
| | 106-97-8 butane |
| | WEL () Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene) |
| 71-36-3 butan-1-ol | |
| WEL () Short-term value: 154 mg/m ³ , 50 ppm Sk | |
| 67-63-0 propan-2-ol | |
| WEL () Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm | |

| | |
|--------------------------------|---|
| Additional information: | The lists valid during the making were used as basis. |
|--------------------------------|---|

Exposure controls
Personal protective equipment:

| | |
|--|---|
| General protective and hygienic measures: | Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes. Avoid contact with the eyes and skin. |
| Respiratory protection: | Not required. |
| Protection of hands: | Not required. |
| Material of gloves | Not required. |
| Penetration time of glove material | Not required. |
| Eye protection: | Tightly sealed goggles. |

9. Physical and chemical properties

Information on basic physical and chemical properties
General Information

| | |
|---|---|
| Appearance: | Form: Aerosol Colour: According to product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | Not applicable, as aerosol. |
| Flash point: | < 0°C (< 32 °F) Not applicable, as aerosol. |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | 240°C (464 °F) |
| Decomposition temperature: | Not determined. |
| Self-igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | Lower: 1.2 Vol % Upper: 26.2 Vol % |
| Vapour pressure at 20°C (68 °F): | 4000 hPa (3000 mm Hg) |
| Density at 20°C (68 °F): | 0.745 g/cm ³ (6.217 lbs/gal) |

| | |
|---|--|
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| Segregation coefficient (n-octanol/water): | Not determined. |
| Viscosity: | Dynamic: Not determined. Kinematic: Not determined. |
| Solvent content: | Organic solvents: 88.5 % |
| EU-VOC: | 679.8 g/l |
| EU-VOC in %: | 91.25 % |
| Solids content: | 11.5 % |
| Other information | No further relevant information available |

10. Stability and reactivity

Reactivity

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available

Incompatible materials: No further relevant information available

Hazardous decomposition products: No dangerous decomposition products known.

11. Toxicological information

Information on toxicological effects

Acute toxicity:

| | | |
|--|--|----------------------------------|
| LD/LC50 values relevant for classification: | 67-64-1 acetone | |
| | Oral | LD50 5800 mg/kg (rat) |
| | Dermal | LD50 20000 mg/kg (rabbit) |
| | LC50 / 4 h | 39 mg/m ³ (rat) |
| | 115-10-6 dimethyl ether | |
| | LC50 / 4 h | 308 mg/m ³ (rat) |
| | 123-86-4 n-butyl acetate | |
| | Oral | LD50 10770 mg/kg (rat) |
| | Dermal | LD50 >17600 mg/kg (rabbit) |
| | LC50 / 4 h | >21.0 mg/m ³ (rat) |
| | 108-65-6 2-methoxy-1-methylethyl acetate | |
| | Oral | LD50 8532 mg/kg (rat) |
| | Dermal | LD50 >5000 mg/kg (rabbit) |
| | LC50 / 4 h | 35.7 mg/m ³ (rat) |
| | 106-97-8 butane | |
| | LC50 / 4 h | 658 mg/m ³ (rat) |
| | 71-36-3 butan-1-ol | |
| | Oral | LD50 4400 mg/kg (rat) |
| | Dermal | LD50 4200 mg/kg (rabbit) |
| | LC50 / 4 h | 25 mg/m ³ (rat) |
| | 67-63-0 propan-2-ol | |
| | Oral | LD50 5045 mg/kg (rat) |
| | Dermal | LD50 12800 mg/kg (rabbit) |
| | LC50 / 4 h | 30 mg/m ³ (rat) |
| | 64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2) | |
| | Oral | LD50 3592 mg/kg (rat) (OECD401) |
| | Dermal | LD50 >3160 mg/kg (rab) (OECD402) |
| | LC50 / 4 h | >15 mg/m ³ (rat) |

Primary irritant effect:

on the skin: No irritant effect

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12. Ecological information

Toxicity

| | | |
|--------------------------|--|----------------------------|
| Aquatic toxicity: | 67-64-1 acetone | |
| | EC50 / 48 h | 39 mg/l (daphnia magna) |
| | LC50 / 48 h | 2262 mg/l (daphnia magna) |
| | LC50 / 96 h (static) | 5540 mg/l (fish) |
| | 115-10-6 dimethyl ether | |
| | EC50 / 48 h | >4000 mg/l (daphnia magna) |
| | 123-86-4 n-butyl acetate | |
| | EC50 / 96 h | 320 mg/l (algae) |
| | LC50 / 24 h | 205 mg/l (daphnia magna) |
| | 108-65-6 2-methoxy-1-methylethyl acetate | |
| | EC50 | 408 mg/l (daphnia magna) |
| | 71-36-3 butan-1-ol | |
| | EC50 / 48 h | 1983 mg/l (daphnia magna) |
| | EC50 / 72 h | 8500 mg/l (algae) |
| | 67-63-0 propan-2-ol | |
| | EC50 / 48 h | 13299 mg/l (daphnia magna) |
| | LC50 / 96 h (dynamic) | 4200 mg/l (fish) |
| | 64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2) | |
| | EC50 / 24 h | 150 mg/l (daphnia magna) |
| | EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| | LC50 / 96 h | 3.77 mg/l (fish) |

Persistence and degradability No further relevant information available

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available

Mobility in soil No further relevant information available

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

Other adverse effects No further relevant information available

13. Disposal considerations

Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system

European waste catalogue 08 01 13 sludges from paint or varnish containing organic solvents or other dangerous substances
 15 01 04 metallic packaging
 15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Uncleaned packaging:
Recommendation Non contaminated packagings may be recycled

14. Transport information
UN-Number
ADR, IMDG, IATA UN1950

UN proper shipping name
ADR 1950 AEROSOLS

IMDG AEROSOLS

IATA AEROSOLS, flammable

Transport hazard class(es)
ADR
Class 2.5F Gases.

Label 2.1

IMDG, IATA
Class 2.1

Label 2.1

Packing group
ADR, IMDG, IATA Void

Environmental hazards: No
Marine Pollutant
Special precautions for user Warning: Gases.

Danger code (Kemler): –

EMS Number: F-D,S-U

Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:
ADR
Limited quantities (LQ) 1L

Transport category 2

Tunnel restriction code D

UN "Model Regulation": UN1950, AEROSOLS, 2.1

15. Regulatory information

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.
R22 Harmful if swallowed.
R36 Irritating to eyes.
R37 Irritating to respiratory system.
R37/38 Irritating to respiratory system and skin.
R41 Risk of serious damage to eyes.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Technical Department

Contact: technical@tygrisindustrial.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent