


LEDinspect PRO SPACE 1000

Inspection lights



1000 lm + 2x500 lm

Bright, white light by high performance LEDs



Rechargeable battery

Operating time of up to 5 h (high) / up to 10 h (low) / up to 12 h (flashing)



Water- and dirt repellent

Protection against the ingress of particles with $\varnothing \geq 1.0$ mm and against splash water according to IP44 / IK06

Product datasheet



Light is versatile

This high-quality inspection lamp was developed especially for professional and private use. For a wide range of applications such as universal use and independently illuminated areas in the garage and workshop. With three light functions, high, low and flashing, 36 LEDs (main light) 2x12 LEDs (side light), 10 Watt and up to 6000 Kelvin and a rechargeable 3.7 V 3600 mAh Lithium battery (main light) / 3.7 V 1800 mAh Lithium battery (side light) this multifunctional light has an operating time up to operating time up to 4 h (strong) / 10 h (weak) / 12 h (flashing). With IP44 & IK06 protection class, this headlight has protection against the penetration of particles with $\varnothing \geq 1.0$ mm and against splash water. This multifunctional LED work light with an extraordinary design is a multidirectional and multivariable lighting system with rotating, swiveling and even removable individual elements, also has a non-slip and dirt-repellent surface, integrated magnets for attachment for hands-free working and is therefore ideally suited as a flexible work light for illuminating engine compartments, vehicle underbodies, garages and workshops. OSRAM also offers a 2-year warranty on this product*.

Product datasheet

Technical data

Product information

Order reference	LEDIL SPACE 1000
Application (Category and Product specific)	LED inspection lights for professionals


Electrical data

Nominal wattage	20.00 W
Nominal voltage	3.7 V

Photometrical data

Color temperature	6000 K
Luminous flux	1000/500 lm
Light color LED	White

Dimensions & weight



Product weight	1680.00 g
Length	262.0 mm
Width	290.0 mm
Height	190.0 mm

Colors & materials

Base color	Black
------------	-------

Lifespan

Guarantee	2 years
-----------	---------

Additional product data

Type of Battery	Rechargeable
-----------------	--------------

Product datasheet

Number of included batteries	n.a.
------------------------------	------

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Certificates & standards

Standards	CE
Type of protection	IP44

Country specific categorizations

Order reference	LEDIL SPACE 1000
-----------------	------------------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	29-12-2021
Primary Article Identifier	4062172092289
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	230d2ede-880c-4ff5-ba49-4c24bafefab

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172092289	INSPECTION LAMP	Folding carton box 1	240 mm x 183 mm x 284 mm	12.47 dm ³	2010.00 g
4062172125932	INSPECTION LAMP	Shipping carton box 4	504 mm x 390 mm x 314 mm	61.72 dm ³	9039.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction LEDinspect PRO FLOODER SPACESHIP 1000

Product datasheet

Application advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.