


# STERLING SAFETYWEAR 2019

WWW.STERLINGSAFETYWEAR.CO.UK

**APACHE**  
INDUSTRIAL FOOTWEAR



**KICK** sizes 6-12 S1P/SRA



**VAULT** sizes 3-12 SB/SRA



**STRIKE NAVY** sizes 6-12 S1P/SRA

WATERPROOF



**MOTION** sizes 6-12 SBP/AE/SRA

NON METALLIC



**ATS MALLORY** sizes 3-13 S1P/SRC

CITY KNIGHTS



**SS500CM** sizes 6-12 S1P/SRC



**SS501CM** sizes 5-12 S1P/SRC

NON METALLIC



**ATS THRUXTON** sizes 3-13 S1P/SRC

NON METALLIC



**ATS OULTON** sizes 3-13 S1P/SRC

NON METALLIC



**ATS PEGASUS** sizes 3-13 S1P/SRC

NON METALLIC



**ATS ORION** sizes 3-13 S1P/SRC

NON METALLIC & WATERPROOF



**ATS ARIZONA** sizes 3-13 S3WR/SRC/HRO



**SS502CM** sizes 6-12 S1P/SRC



**SS503CM** sizes 6-12 S1P/SRC

NON METALLIC & WATERPROOF



**ATS DAKOTA** sizes 3-13 S3WR/SRC/HRO



**AP300** sizes 3-14 S3/SRA



**AP302SM** sizes 3-12 S1P/SRA



**AP314CM** sizes 6-12 S3/SRA



**AP315CM** sizes 6-12 S3/SRA

MEN'S EXECUTIVE



**SS100** sizes 3-12 SB

LADIES NON METALLIC



**SS620CM** sizes 3-8 S1P/SRC

WATERPROOF



**AP305** sizes 5-13 S3/WR/SRA



**FLYWEIGHT DEALER** sizes 6-12 S3/SRA

NON METALLIC & WATERPROOF



**COMBAT** sizes 5-12 S3/WR/SRC/HRO



**AP306** sizes 3-14 S3/SRA



**AP318SM** sizes 6-12 S1P/SRA

STERLING STEEL



**SS806SM** sizes 3-12 S1P/SRC



**SS807SM** sizes 6-12 S1P/SRC

WATERPROOF



**RANGER BLACK** sizes 5-13 S3/WR/SRA

WATERPROOF



**RANGER BROWN** sizes 5-13 S3/WR/SRA



**AP714SM** sizes 6-13 S3/SRA



**AP715SM** sizes 6-13 S3/SRA



**SS819CM** sizes 5-13 S3/SRA



**SS400SM** sizes 3-13 S1P/SRA



**SS402SM** sizes 4-12 S1P/SRA



**SS600SM** sizes 5-13 S1P/SRA



**SS601SM** sizes 5-13 S1P/SRA



**SS604SM** sizes 5-12 S1P/SRC

Airside



**SS704CM** sizes 3-13 S3/SRA

NON METALLIC FOOTWEAR



**SS705CM** sizes 3-13 S3/SRA

STERLING Waterproof



**SS812SM** sizes 3-13 S3WR/SRC

WATERPROOF



**SS813SM** sizes 5-12 S3WR/SRC



**SS607SM** sizes 6-12 SBP/SRA



**SS609SM** sizes 5-12 S3/SRC



**SS613SM** sizes 3-13 S1P/SRA

PVC WELLINGTON WATERPROOF



**SS628SM** sizes 5-14 S5/SRC

PVC RIGGER BOOT WATERPROOF



**SS630SM** sizes 5-14 S5/SRC



**SS403SM** sizes 5-13 S1P/SRA

## SAFETY RATINGS EN ISO 20345 :2011

<b>SB</b>	Basic safety protection. 200 joule toe cap.	<b>S2</b>	200 joule toe cap. Closed seat region. Anti-static. Energy absorption. Water absorption.	<b>S4</b>	200 joule toe cap. All rubber or all polymeric anti-static footwear. Energy absorption.
<b>SB, P</b>	Basic safety protection. 200 joule toe cap. Penetration resistant midsole.	<b>S3</b>	200 joule toe cap. Closed seat region. Anti-static. Energy absorption. Penetration resistant midsole. Water absorption and penetration resistant. Cleated outsole.	<b>S5</b>	200 joule toe cap. All rubber or all polymeric anti-static footwear. Energy absorption. Penetration resistant midsole. Cleated outsole.
<b>S1</b>	200 joule toe cap. Closed seat region. Anti-static. Energy absorption.	<b>S1, P</b>	200 joule toe cap. Closed seat region. Anti-static. Energy absorption. Penetration resistant midsole.	<b>HRO</b>	Heat Resistant Outsole 300°C.

## SLIP RESISTANCE

<b>SRA</b>	Footwear is tested on clay tiles with sodium lauryl sulphate solution and meets a minimum Coefficient (CoF) of Friction of 0.32 tested flat & CoF 0.28 tested at the heel.	<b>SRB</b>	Footwear is tested on stainless steel with a glycerol solution and meets a CoF of 0.18 tested flat & 0.13 tested at the heel.
<b>SRC</b>	Footwear indicates both SRA & SRB are met.		

Slip resistance is tested in accordance with EN ISO 20345  
Sterling Safetywear Ltd reserve the right to change specification without prior notice.

## KEY

- petrol & chemical resistant
- oil resistant
- heat resistant
- double density shock absorption
- 200 joule toecap
- antistatic
- water resistant
- penetration resistant midsole